



P.O. Box 1088 □ Roseburg, OR 97470
 Ph: 541-679-3311 □ Fax: 541-679-2543
 Website: www.rfpco.com

MATERIAL SAFETY DATASHEET

Complies with ANSI Z400.1 format

HMIS Label

Health (potential chronic effects)	1*
Fire Hazard	0
Reactivity	0
Personal Protection – depends on usage	See Section 8

PRODUCTS: Roseburg Melamine Formaldehyde Bonded Composite Panel

Roseburg Forest Products

Date of Preparation: rev. 7/08

Section 1 General Information

Chemical Name & Synonyms: SkyBlend Particleboard (SkyBlend Particleboard, SkyBlend FSC Particleboard, SkyBlend Dura Shelf, SkyBlend FSC DuraShell) SkyBlend MDF, SkyBlend MDF Plus

Description: A panel product manufactured from particles of wood bonded together with melamine formaldehyde resins.

Chemical Family: Wood

Formula: Mixture

Manufacturers Name: Roseburg Forest Products Co.
 P.O. Box 1088
 Roseburg, Oregon 97470

Prepared by: Roseburg Forest Products and
 DeEtta Burrows, MSPH, CIH – Wise Steps, Inc.

For Information Contact:
 Quality Assurance Director (541) 679-3311

Section 2 Composition of Ingredients¹

Chemical Name (Ingredients): Particleboard

	PERCENTAGE	OSHA PEL	OSHA STEL	ACGIH TLV-TWA	ACGIH TLV-STEL
Wood Fiber*	95 - 98%	15 mg/m ³	None	1 mg/m ³ inhalable	None

The product may release small quantities of formaldehyde in gaseous form. Emissions decrease through time as the panels age. Manual or mechanical cutting or abrasion processes performed on the product can result in generation of wood dust. For anyone needing the ASTM E-133 formaldehyde chamber test data contact Roseburg Forest Product Quality Assurance Director at 541-679-3311.

* Exposure to wood dust, except for western red cedar: 2.5 mg/m³ (OSHA), 0.5 mg/m³ (l) TLV

Section 3 Toxicology and Health Information

Acute: Wood dust can irritate the eyes and breathing passages. Some wood species may cause skin and respiratory irritation. The irritation is generally caused by mechanical action on the skin or mucous membranes. Chemical effects from some wood species can result in respiratory allergies. Respiratory ailments have included bronchitis, impairment of breathing functions, and asthma. These products may release very small quantities of formaldehyde in a gaseous state. Formaldehyde may be irritating to the eyes, nose, throat and skin.

¹ Notes: OSHA = Occupational Safety & Health Administration
 ACGIH = American Conference of Governmental Industrial Hygienists
 PEL = Permissible Exposure Limit
 TWA = Time Weighted Average
 TLV = Threshold Limit Value – recommended level
 STEL = Short Term Exposure Limit (15-minutes)
 C = Ceiling Limit, never to be exceeded

Chronic: Wood dust, depending on the species, may cause allergic contact dermatitis and respiratory sensitization with prolonged, repetitive contact or exposure to elevated dust levels. Prolonged exposure to some wood species dust has been reported to be associated with nasal cancer.

Target Organs: Eyes, skin, mucous membranes, upper respiratory tract.

Section 3 Toxicology and Health Information *(continued)*

Carcinogenicity Listing: NTP known to be a Human Carcinogen (10th Report), IARC Monographs: Wood dust, Group 1 - IARC Group 1: Carcinogenic to humans; sufficient evidence of carcinogenicity. This classification is primarily based on studies showing an association between occupational exposure to wood dust and adenocarcinoma of the nasal cavities and paranasal sinuses. IARC did not find sufficient evidence of an association between occupational exposure to wood dust and cancers of the hypopharynx, oropharynx, lymphatic and hematopoietic systems, lungs, stomach, colon or rectum.

Medical Conditions That May Be Aggravated by Exposure: Wood dust may aggravate preexisting respiratory conditions or allergies. Formaldehyde in even trace amounts may aggravate existing respiratory problems and cause allergies to susceptible persons.

Routes of Entry: Inhalation and skin contact

Section 4 Emergency First Aid

Inhalation: Remove from area to fresh air. Seek medical attention if persistent irritation, severe coughing or breathing difficulty occurs.

Eye Contact: Immediately flush eyes with copious amounts of water for at least 15 minutes. Assure adequate flushing of the eyes by separating the eyelids with fingers. Seek medical care if irritation persists.

Skin Contact: Wood dust of certain species may elicit allergic contact dermatitis in sensitized individuals and can cause mechanical irritation. Wash affected areas with soap and water. Seek medical attention if rash, irritation or dermatitis persists.

Ingestion: Not applicable under normal use.

Section 5 Fire and Explosion Hazard

Flash point (Method Used)	Flammable limits	LEL	UEL
Not Applicable			Not Applicable

Auto Ignition Temperature: Not Applicable (will depend upon duration of exposure to heat source and other variables.)

Extinguishing Media: Water, carbon dioxide, sand.

Special Fire Fighting Procedures: Self-contained breathing apparatus (SCBA) recommended when fighting fire.

Unusual Fire & Explosion: Wood dust from sawing, sanding, or machining can be explosive in the presence of an ignition source depending on particle size and moisture content. Airborne concentrations of 40 grams per cubic meter are often used as the lower explosive limit (LEL) for wood dusts.

Section 6 Accidental Release Measures

Steps to be Taken in Case Material is Released or Spilled: Not applicable for products in purchased form. Wood dust generated from sawing, sanding, or machining may be vacuumed or shoveled for recovery or disposal. Avoid dusty conditions and provide good ventilation. Use NIOSH/MSHA-approved respiratory protection and goggles where exposure limits may be exceeded.

Section 7 Storage and Handling

Storage Precautions: No special storage precautions. Handling can result in wood splinters.

Other Precautions: Avoid repeated or prolonged inhalation of wood dust. No special handling precautions are warranted for products in purchased form.

Section 8 Exposure Controls & Personal Protection

Required Ventilation: Provide local exhaust ventilation as needed so that exposures are below exposure limits.

Respiratory Protection: Generally would not be needed for products in purchased form. Wear NIOSH/MSHA approved respirator when the allowable dust exposure limits may be exceeded.

Protective Gloves: Not required. Cloth, canvas or leather gloves are recommended for protection against mechanical irritation.

Eye Protection: Goggles or safety glasses are recommended when manufacturing, machining, sawing or sanding product.

Other: None required for product in purchased form. Other protective equipment, such as gloves and outer garments, may be needed depending on dust conditions.

Section 9 Physical & Chemical Properties

Boiling Point (F°): Not applicable

Solubility in Water: Not applicable

Vapor Pressure (MM Hg): Not applicable

pH: Not applicable

% Volatiles by Volume (@70°F(21°C)): 0

Evaporation Rate: Not applicable
(Butyl Acetate = 1)

Vapor Density (air =1): Not applicable

Spec Gravity (H₂O=1): 1, variable depends on wood species and moisture

Appearance and Odor: Light tan to dark tan. Color and odor are dependent upon wood species.

Section 10 Stability and Reactivity

Stability: Stable under normal conditions

Conditions to Avoid (Incompatibilities): Avoid contact with oxidizing agents. Avoid open flame. Product may ignite at temperatures in excess of 400°F (204°C).

Hazardous Decomposition Products: Thermal and/or thermal-oxidative decomposition (fire) can produce irritating toxic fumes and gases, including carbon monoxide, hydrogen cyanide, aldehydes, organic acids, polynuclear aromatic compounds and nitrogen oxides.

Hazardous Polymerization: Not applicable

Section 11 Toxicological Information

Data not available for product in purchased form. Individual component information is listed below if available.

Wood dust (softwood or hardwood) OSHA Hazard Rating = 3.3; moderately toxic with probable oral lethal dose to humans being 0.5-5g/kg (about 1 pound for a 70 kg or 150 pound person) Source: OSHA Regulated Hazardous Substances, Government Institutes. Inc., February 1990.

Section 12 Ecological Information

No information available at this time. As with all foreign substances do not allow to enter the storm drainage systems.

Section 13 Waste Disposal

Follow safe solid waste disposal guidelines in accordance with federal, state and local regulations. If disposed of or discarded in its purchased form, incineration is the preferred method. Dry land disposal is acceptable in most states. It is however, the user's responsibility to determine at the time of disposal whether your product meets RCRA criteria for hazardous waste.

Section 14 Transportation Information

Not regulated as a hazardous material by the U.S. Department of Transportation.

Section 15 Regulatory Information

Particleboard certified as meeting the Department of Housing and Urban Development (HUD) Manufacturing Home Construction and Safety Standards, 24 CFR Part 3280, does not permit in excess of 0.3 ppm formaldehyde when tested in accordance with ASTM E1333-90, Large Scale Test method for Determining Formaldehyde Emissions from Wood Products. Particleboard underlayment products are not permitted to exceed 0.2 ppm emission rates. These products emit less than 0.2 parts per million formaldehyde.

Minnesota Statutes 1984 Section 144.495 and 325 F.18 required that all particleboard and medium-density fiberboard sold or used in Minnesota meet the HUD Formaldehyde Emissions Standard, 24 CFR Sections 3280.308 and 3280.406.

California's Safe Drinking Water and Toxic Enforcement Act of 1986 (Initiative Measure, Proposition 65): Title 22 California Code of Regulations requires that a clear and reasonable warning be given before exposure to chemicals listed by the State as causing cancer or reproductive toxicity. Formaldehyde is on California's list of chemicals known to the State to cause cancer.

No reportable chemicals per SARA Title III Section 313.

Section 16 Other Information

HMIS Hazard Rating (0- Insignificant, 1- Slight, 2- Moderate, 3- High, 4- Extreme)

Health – 1* (potential chronic effects) Flammability - 0 Reactivity - 0

Personal Protective Equipment – Depends on Use.

Disclaimer

Roseburg Forest Products believes the information contained in this MSDS to be accurate at the time of preparation and has been compiled using sources believed to be reliable. However, Roseburg Forest Products makes no warranty, either expressed or implied, concerning the accuracy or completeness of the information presented. It is the responsibility of the user to comply with local, state, and federal regulations concerning use of this product. It is the further responsibility of the buyer to research and understand safe methods of storing, handling and disposal of this product.